

# Projet® MJP 2500 Plus and 3600 Dental

High throughput productivity Multijet Printing of precision wax-ups, models and surgical guides



**Projet MJP 2500 Plus**




**Projet MJP 3600 Dental**

<b>Printing Modes</b> HD Mode UHD Mode HDX Mode HDP Mode	High Definition	Ultra High Definition High Definition Smooth (drill guides, jaw models and orthodontic thermoforming models) High Definition Plaster (plaster-like appearance for crown and bridge, partial denture and orthodontic models)
<b>Net Build Volume (xyz)*</b>	11.6 x 8.3 x 5.6 in (295 x 211 x 142 mm)	11.2 x 7.3 x 8 in (284 x 185 x 203 mm)
<b>Resolution (xyz)</b> HD Mode UHD Mode HDX Mode HDP Mode	800 x 900 x 790 DPI; 32 µ layers	750 x 750 x 890 DPI; 29 µ layers 375 x 450 x 790 DPI; 32 µ layers 375 x 450 x 790 DPI; 32 µ layers
<b>Accuracy (typical)</b> of part dimension	±0.004 inch per inch (±0.1016 mm per 25.4 mm)	±0.001-0.002 inch per inch (0.025-0.05 mm per 25.4 mm)
Accuracy may vary depending on build parameters, part geometry and size, part orientation, and post-processing.		
<b>Build Materials</b> HD Mode UHD Mode HDX Mode HDP Mode	Visijet M2R-TN** – Rigid Tan	Visijet M3 Dentcast Visijet M3 Dentcast, Visijet M3 Stoneplast, Visijet M3 PearlStone Visijet M3 Dentcast, Visijet M3 Stoneplast, Visijet M3 PearlStone
<b>Support Material</b>	Visijet M2 SUP	Visijet S300
<b>Material Packaging</b>	Build materials: In clean 3.30 lbs (1.5 kg) bottles (printer holds up to 2 build materials bottles with auto-switching) Support materials: In clean 3.08 lbs (1.4 kg) bottles (printer holds up to 2 support material bottles with auto-switching)	Build and support materials in clean 4.41 lbs (2 kg) bottles (printer holds up to 2 of each with auto-switching)
<b>Electrical</b>	100-127 VAC, 50/60 Hz, single-phase, 15A 200-240 VAC, 50 Hz, single-phase, 10A Single C14 receptacle	100-127 VAC, 50/60 Hz, single-phase, 15A 200-240** VAC, 50 Hz, single-phase, 10A
<b>Dimensions (WxDxH)</b> 3D Printer Crated 3D Printer Uncrated	55 x 36.5 x 51.7 in (1397 x 927 x 1314 mm) 44.1 x 29.1 x 42.1 in (1120 x 740 x 1070 mm)	32.5 x 56.3 x 68.5 in (826 x 1430 x 1740 mm) 29.5 x 47 x 59.5 in (749 x 1194 x 1511 mm)
<b>Weight</b> 3D Printer Crated 3D Printer Uncrated	716 lb (325 kg) 465 lb (211 kg)	955 lbs (433 kg) 659 lb (299 kg)
<b>3D Sprint™ Software</b>	Easy build job set-up, submission and job queue management; Part stacking and nesting capability; Extensive part editing tools;	Automatic part placement and build optimization tools; Automatic support generation; Job statistics reporting tools
<b>E-mail Notice Capability</b>	Yes	Yes
<b>Internal Hard Drive Capacity</b>	500 Gb minimum	500 Gb minimum
<b>Connectivity</b>	Network ready with 10/100/1000 BaseT Ethernet interface USB port	Network ready with 10/100 Ethernet interface Front panel USB Port
<b>Client Hardware Recommendation</b>	CPU: 3 GHz multiple core processor (2 GHz Intel® or AMD® processor mini) with 8 GB RAM or more (4 GB mini), OpenGL 3.2 and GLSL 1.50 support (OpenGL 2.1 and GLSL 1.20 mini) RAM: 1 GB video or more, 1280 x 1024 (1280 x 960 mini) screen resolution or higher HARD DRIVE: SSD or 10,000 RPM hard disk drive (30 GB of available hard-disk space for cache mini) OTHER: Google Chrome or Internet Explorer 11 (Internet Explorer 9 mini), Microsoft .NET Framework 4.5 installed with application	CPU: Multiple core processor. Hyper-threading and clock speeds above 3GHz can be beneficial but should be paired with a good balance of cores RAM: 8 GB of more. HARD DISK: SSD. Multiple core processor OTHER: Google Chrome or Internet Explorer
<b>Client Operating System</b>	Windows® 7, Windows 8 or Windows 8.1 (Service Pack)	Windows® 7, 8 and 8.1 (service pack)
<b>Input Data File Formats Supported</b>	STL, CTL, OBJ, PLY, ZPR, ZBD, AMF, WRL,	3DS, FBX, IGES, IGS, STEP, STP, MJPPDD
<b>Post-Processing</b>	MJP EasyClean System for removal of wax supports	Projet Finisher for removal of wax supports (optional)
<b>Operating Temperature Range</b>	64-82 °F (18-28 °C), reduced print speed at > 77 °F (25 °C)	64-82 °F (18-28 °C)
<b>Operating Humidity</b>	30-70 % Relative Humidity	30-70 % relative humidity
<b>Noise</b>	< 65 dBa estimated (at medium fan setting)	< 65 dBa estimated (at medium fan setting)
<b>5-Year Printhead Warranty</b>	Optional	Standard
<b>Certifications</b>	CE	CE

# Visijet® Dental Materials

For castable and pressable wax-ups, precision dental models and surgical guides



Properties	Condition	Visijet M2R-TN	Visijet M3Dentcast	Visijet M3 PearlStone	Visijet M3 Stoneplast	Visijet M2 SUP	Visijet S300
Composition		UV Curable Plastic				Wax Support Material	
Color		Opaque Tan	Dark green	White	Natural	White	White
Bottle Quantity		1.5 kg	2 kg	2 kg	2 kg	1.4 kg	2 kg
Density @ 80 °C		1.16 g/cm³	102 g/cm³	104 g/cm³	102 g/cm³	N/A	N/A
Tensile Strength	ASTM D638	60-70 MPa	32 MPa	40 MPa	41 MPa	N/A	N/A
Tensile Modulus	ASTM D638	2500-3000 MPa	1724 MPa	1794 MPa	1850 MPa	N/A	N/A
Elongation at Break	ASTM D638	6-12 %	12.3%	7.7%	17%	N/A	N/A
Flexural Strength	ASTM D790	90-100 MPa	45 MPa	N/A	51 MPa	N/A	N/A
Heat Distortion Temperature	ASTM D648 @ 0.45 MPa	71 °C	N/A	88 °C	56 °C	N/A	N/A
Ash Content		N/A	0.01%	N/A	N/A	N/A	N/A
Melting Point		N/A	N/A	N/A	N/A	60 °C	60 °C
Softening Point		N/A	N/A	N/A	N/A	40 °C	40 °C
USP Class VI Certified*		-	No	No	Yes	N/A	N/A
Printer Compatibility		Projet MJP 2500 Plus	Projet MJP 3600 Dental	Projet MJP 3600 Dental	Projet MJP 3600 Dental	Projet MJP 2500 Plus	Projet MJP 3600 Dental
Description		High modulus, rigid plastic (tan) for dental models	Wax-up castable material	Solid stone appearance	Translucent or stone finish**	Non-toxic wax material for hands-free melt-away supports	

\* DISCLAIMER: Material is capable of meeting the requirements of USP Class VI testing. It is the responsibility of each customer to determine that its use of any Visijet® material is safe, lawful and technically suitable to the customer's intended applications. The values presented here are for reference only and may vary. Customers should conduct their own testing to ensure suitability for their intended application.

\*\* Choice of finish requires additional post processing.

[www.3dsystems.com](http://www.3dsystems.com)



Warranty/Disclaimer: The performance characteristics of these products may vary according to product application, operating conditions, material combined with, or with end use. 3D Systems makes no warranties of any type, express or implied, including, but not limited to, the warranties of merchantability or fitness for a particular use.

© 2017 by 3D Systems, Inc. All rights reserved. Specifications subject to change without notice. 3D Systems, Projet and Visijet are registered trademarks and the 3D Systems logo is a trademark of 3D Systems, Inc.